

Application No. 10/611,947

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) An airbag module comprising an inflator, an airbag and at least one substantially tape or cord shaped measuring element, a first end of the at least one substantially tape or cord shaped measuring element is connected to an interior surface of the airbag and a second end of at least one substantially tape or cord shaped measuring element is arranged in a storage device for the measuring element, whereby between the first and the second ends of the at least one substantially tape or cord shaped measuring element is located a measuring device for the measurement of one or more of the advance movement distance, the advance movement velocity [[and/]]or the advance movement time of the measuring element, and whereby a tensioning device for the measuring element is arranged between the measuring device and the second end, or at the second end, to tighten the measuring element between the first end and the measuring device prior to a deployment of the airbag.

wherein the storage device for the measuring element is a sleeve or sheath formed of at least one flexible or spiral shaped cable connected at one end directly to an airbag housing module, each cable comprising at least one longitudinally extending sleeve or sheath chamber extending along the length of the cable for storing one of the at least one substantially tape or cord shaped measuring elements per chamber.

2. (withdrawn) The airbag module according to claim 1, wherein the tensioning device for the measuring element is a second tape or cord shaped element, which is connected to the measuring element within the airbag module and projects out of an airbag housing.

Application No. 10/611,947

3. (withdrawn) The airbag module according to claim 2, wherein the second element is connected to the measuring element in a detachable manner.

4. (withdrawn) The airbag module according to claim 1, wherein the tensioning device for the measuring element is a spring-like tensioning device.

5. (withdrawn) The airbag module according to claim 4, wherein the spring-like tensioning device comprises a locking device.

6. (cancelled)

7. (cancelled)

8. (currently amended) The airbag module according to claim [[6]] 1, wherein the measuring element is arranged in the sleeve or sheath in a single layer.

9. (currently amended) The airbag module according to claim [[6]] 1, wherein the sleeve or sheath comprises several parts along a longitudinal direction thereof.

10. (cancelled)

11. (cancelled)

12. (original) The airbag module according to claim 1, wherein the airbag module comprises a deceleration device for decelerating the movement of the measuring element.

Application No. 10/611,947

13. (withdrawn) The airbag module according to claim 12, wherein the deceleration device is arranged to interact with the measuring device.

14. (original) The airbag module according to claim 12, wherein the deceleration device is arranged on the storage device.

15. (original) The airbag module according to claim 14, wherein the deceleration device is an indented region of the sleeve or sheath.

16. (original) The airbag module according to claim 14, wherein the deceleration device is a spring loaded bracket.

17. (original) The airbag module according to claim 14, wherein the deceleration device is a roughened inner surface of the sleeve or sheath.

18. (withdrawn) The airbag module according to claim 1, wherein the measuring element is provided with a detectable code, which can be detected by the measuring device in a capacitive, inductive, optical or mechanical manner.

19. (withdrawn) The airbag module according to claim 1, wherein the airbag module has a test opening therein to check the tightened state of the measuring element by a test device.

20. (withdrawn) The airbag module according to claim 19, wherein the measuring element comprises a code for indicating its tightened state, which in the tightened state of the measuring element is aligned with the test opening.

Application No. 10/611,947

21. (withdrawn) The airbag module according to claim 1, wherein the tightened state of the measuring element can be controlled by the measuring device.

22. (original) The airbag module according to claim 1, wherein the second end of the measuring element comprises a code.